Canister Extractor





Portable low and adjustable pressure canister carpet extractor make quick work in tight areas.

Simple maintenance, easy mobility

Get quick, easy access to working parts with the convenient clamshell design. The extractor's large rear wheels increase mobility and allow for easier transportation on stairs.

Low cost life-cycle

Strong and robust construction means years of dependable use. The unique bladder design maximizes solution/recovery while minimizing the unit's footprint.

Key Benefits

- Straightforward, simple design makes this unit easy to use and maneuver
- Patented bladder design keeps machine compact
- Standard 100 psi /6.9 bar unit is easy to transport and perfect for cleaning in both tight or open spaces

tel: +1-763-540-1315

fax: +1-763-513-2144



Canister Extractors



Features	Specifications*	
Product Name	EX-CAN-57-LP (low pressure)	220 V
Solution System Solution pump pressure Solution pump voltage Solution pump amps Solution pump open flow rate	100 psi / 6.9 bar 120 V 1 A 1.8 gpm / 6.81 L/min	.5 A
Vacuum System Airflow at 2 in / 50 mm orifice Water lift at sealed orifice Vacuum motor type	101 ft ³ / 2.8 m ³ /h 137 in / 3480 mm Single speed, tangential discharge, 5.7 in / 145 mm diameter, dual ball bearings, epoxy painted fan case; recognized by UL	
Vacuum motor power Vacuum motor stages Vacuum motor voltage Vacuum motor amps	1.66 hp / 1.23 kW 3 stage 120 V AC 13 A	6.8 A
Tank Capacity Solution tank capacity Recovery tank capacity	15 gal / 56.7 L 19 gal / 71.9 L	
Chassis/Body Construction Construction type Caster diameter (locking) Wheel diameter	Rotationally-molded polyethylene 4 in / 100 mm 12 in / 305 mm	
Power Cord Power cord length Power cord type	25 ft / 7.6 m, 1 cord 14 gauge 3 wire SJTO, recognized by UL and CSA, safety yellow, detachable	
Standard Tools/Accessories Tool/accessory description	Low pressure (EX-CAN-15 LP) 13 in / 330 mm floor tool with three spray jets, stainless steel wand/shoe, 15 ft \times 1.5 in / 4.5 m \times 380 mm vacuum hose, 15 ft \times 3/8 in 4.5 m \times 90 mm solution hose Contact your sales representative or authorized distributor for information on additional accessories.	
Dimensions/Weight/Sound Level Length/Width/Height/Weight/Sound	L: 38 in / 965 mm, W: 19 in / 482 mm, H: 38 in / 965 mm, Wt: 110 lb / 49.8 kg, 82 dBA	
Warranty	See your sales representative or authorized distributor for complete warranty details.	

^{*}Specifications subject to change without notice Note: All 120V models will come with a dual Tennant/Nobles decal

not yet registered in the United States.

tel: +1-763-540-1315

fax: +1-763-513-2144